

TEMPERED LPG (TLP) Safety Data Sheet (SDS)

LPG-BUS-HSE-IST-0009 / LPG366
Released 28 February 2019. Version 9.0

1 Product and Company Details

1.1 Product Identifier

Product Name	Tempered Liquefied Petroleum Gas (TLP)
Proper Shipping Name	Compressed Gas Flammable N.O.S. Note: Origin Energy distributes via piping systems, this product is not normally transported or shipped in containers.
Other Names	TLP; Tempered LP Gas

1.2 Recommended use and restrictions on use

Use(s)	As fuel in domestic and commercial gas appliances
Restrictions	Not to be concentrated and intentionally inhaled.

1.3 Supplier details

Company	Origin Energy LPG Limited Level 32 Tower 1, 100 Barangaroo Avenue, Barangaroo NSW 2000 Website: www.originenergy.com.au/lpg
Enquiries	General and Technical Information 133 LPG (133 574)
Emergency Telephone	1800 808 526 all hours


2 Hazards identification

2.1 Classification of the substance or mixture

TLP as supplied by Origin contains less than 0.1% of 1,3 Butadiene. As a “flammable compressed gas”, TLP is classified as a Dangerous Good by the Australian Dangerous Goods Code.

GHS Classification	Flammable Gases: Category 1 Gases under pressure: Compressed gas
--------------------	---

2.2 Label Elements

Signal word	Danger
Pictogram	
Hazard statement(s)	H220 Extremely flammable gas
Prevention Statements(s)	H280 Contains gas under pressure, may explode if heated P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking
Response Statement(s)	P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely P381 Eliminate all ignition sources if safe to do so.
Storage statement	P410 + P403 Protect from sunlight. Store in a well-ventilated place.
Disposal Statement	None allocated

2.3 Other Hazards

Asphyxiant. Effects are proportional to oxygen displacement.
Smell: People with poor or no sense of smell should be made aware of the risk in the event of a gas leak.

3 Composition and Information on Ingredients

3.1 Substance / Mixtures		
Ingredient	CAS Number	Content v/v
Propane	0074-98-6	7 - 26%
Propene	115-07-1	0 – 20%
Butane (mixture of “n” and “iso” isomers)	106-97-8	0 – 1%
1,3 Butadiene	106-99-0	<0.1%
Ethyl Mercaptan (Odorant)	75-08-1	Approx. 25mg/kg
Air	74%	
Alternative Names: TLP or Tempered LP Gas	UN Number 1954	

4 First Aid

4.1 Description of first aid measures	
Eye	Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart for 15 minutes. Seek medical attention.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained \Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 131126 (Australia Wide) or a doctor.
Skin	Cold burns: Remove contaminated clothing and gently flush the affected areas with warm water (30°C) for 15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention.
Ingestion	Due to product form and application, ingestion is considered unlikely.
First aid facilities	Eye wash facilities and / or safety shower should be available. This will depend upon the nature of use and associated risks.

4.2 Most important symptoms and effects, both acute and delayed

In high concentrations, may cause asphyxiation. Direct contact with escaping compressed gas may cause frostbite injury.

4.3 Immediate material attention and special treatment needed

Treat symptomatically

5 Fire Fighting Measures

5.1 Extinguishing media

Stop flow of gas if safe to do so, such as by closing the supply valve as appropriate to the event.

5.2 Special hazards arising from the substance or mixture

Extremely flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing switches / tool, heaters, naked lights, pilot lights, mobile phones etc. when handling.

5.3 Advice for fire-fighters

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected

location. Do not extinguish flame if resulting escape of gas poses greater risk. Do not approach cylinder or containers suspected of being hot. This material is capable of forming explosive mixtures in air.

5.4 Hazchem code

2YE

2 Fine Water Spray

S Risk of violent reaction or explosion. Wear full kit and breathing apparatus. Dilute.

E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6 Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder or piping system is leaking, evacuate area of personnel. Inform manufacturer / supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS. Ventilate area where possible and eliminate ignition sources.

6.2 Environmental precautions

Prevent from entering sewers, basements and work pits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Keep unnecessary people away, isolate hazard area. Stop the flow of material, if this is without risk. If the leak is from a cylinder, move the cylinder to a safe and well ventilated area, and allow to discharge. Keep the area evacuated and free from ignition sources until any leak has stopped.

6.4 Reference to other sections

See section 8 and 13 for exposure controls and disposal

7 Handling and Storage

7.1 Precautions for safe handling

For cylinders: Before use carefully read the product label.

All applications: Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating, prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible substances and sources of ignition. Cylinders should be stored: upright, prevented from falling, in a secure area: below 45°C in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end use(s)

No information provided

8 Exposure Controls and Personal Protection

8.1 Control parameters

Exposure Standards

Ingredient	Reference	TWA	
Propane	ACGIH TLV	1000 ppm 8 hours	Asphyxiant
Propene	ACGIH TLV	500 ppm 8 hours	Asphyxiant
Butane	NOHSC	800 ppm 8 hours	Asphyxiant

Biological limits: No biological limits have been entered for this product

8.2 Exposure Controls

Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended.
PPE – Eye / Face	Wear safety glasses
PPE – Hands	Wear insulated or leather gloves
PPE – Body	Wear non-static long sleeved shirts and trousers, or coveralls

9 Physical and Chemical Properties

9.1 Physical Description / Properties

Appearance	Colourless gas
Odour	LP Gas is normally an odourless gas. Ethyl Mercaptan is added to LPG prior to mixing with air at prescribed quantities to give a distinctive odour to warn of the presence of gas.
Flammability	Extremely flammable
Boiling Point	Not applicable
Flash Point	Not applicable
Melting Point	Not applicable
Auto Ignition Temperature	494°C - 550°C
Evaporation Rate	Not applicable
pH	Not applicable
Specific Gravity Liquid	Not applicable
Relative Vapour Density	1.15 (Air = 1)
Solubility (water)	Not applicable
Partition coefficient	Not available
Vapour Pressure (at 40°C)	Not applicable
Upper explosive limit	23%
Lower explosive limit	9%
Decomposition temperature	Not available
Viscosity	Not available
Oxidising Properties	Not available
Odour threshold	Not available

9.2 Other Information

% Volatiles	100% (other than air)
-------------	-----------------------

10 Stability and Reactivity

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6

10.2 Reactivity

Stable under recommended conditions of storage

10.3 Possibility of hazardous reactions

Polymerization will not occur

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorite), acids, (e.g. Nitric acid), heat and ignition sources. DO NOT use natural rubber flexible hoses. Also incompatible (potentially violently) with oxygen, halogens and metal halides. Compatible with most common metals.

10.6 Hazardous decomposition products

This material will not decompose to form hazardous products other than that already present.

11 Toxicological Information**11.1 Information on toxicological effects**

Acute toxicity	No known toxicological effects from this product. Based on available data, the classification criteria are not met.
Skin	Not classified as a skin irritant. Contact with the escaping compressed gas may cause frostbite injury.
Eyes	Not classified as an irritant to the eyes. Contact with the escaping compressed gas may cause frostbite injury.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Not classed as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Not classified as a reproductive toxin
STOT – single exposure	Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness, drowsiness, weakness, fatigue, breathing difficulties and unconsciousness.
Aspiration	Not classified as causing aspiration

12 Ecological Information**12.1 Toxicity**

No information provided

12.2 Persistence and degradability

No information provided

12.3 Bio-accumulative potential

No Information provided

12.4 Mobility in soil

No information provided


12.5 Other adverse effects

No known ecological damage is caused by this product

13 Disposal Considerations**13.1 Waste treatment methods**

Waste disposal	Cylinders should be returned to the supplier for disposal of contents. Compressed Gas cylinders should be returned to the owning organisation stamped on the cylinder when no longer required.
Legislation	Dispose of in accordance with the relevant local legislation.

14 Transport Information

Classified as a Dangerous Good by the criteria if the ADG code			
	Land Transport (ADG)	Sea Transport (IMDG / IMO)	Air Transport (IATA / ICAO)
14.1 UN Number	1954	1954	1954
14.2 Proper Shipping Name	Compressed gas, flammable N.O.S.	Compressed gas, flammable N.O.S.	Compressed gas, flammable N.O.S.
14.3 Transport Hazard Class	2.1	2.1	2.1
14.4 Packing Group	None allocated	None allocated	None allocated
Alternative Names			
Tempered LP Gas; TLP			
14.5 Environmental hazards			
No information provided			
14.6 Special precautions for user			
Hazchem Code	2SE.		
GTEPG	2A2.		
EMS	F-D, S-U		
Other Information	Ensure cylinders is separated from driver and that outlet of relief valve device is not obstructed. Cylinders must be secured in an upright position fro transport. Transport in accordance with the requirements of ADG Code and the Load Restraint Guide.		

15 Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture	
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	SafeWork Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals. The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)]
Hazard Codes	F+ Extremely flammable
Safety phrases	S9 Keep container in a well-ventilated place S16 Keep away from sources of ignition – No smoking
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances). All components are listed on AICS or are exempt

16 Other Information

16.1 Additional Information

The storage of significant quantities of gas cylinders must comply with AS4322 The storage and handling of gases in cylinders; and AS/NZS 1596 The storage and handling of LP Gas.

Asphyxiants (1)	When present in the atmosphere in high concentrations, asphyxiants reduce the oxygen concentration by displacement. Atmospheres deficient in oxygen do not provide sensory warning of danger and most simple asphyxiants are odourless. Therefore, it is not appropriate to recommend an exposure standard for each asphyxiant, but to maintain oxygen concentrations. However, some asphyxiants may be given an exposure standard due to the potential for narcotic effects at high concentrations or an explosion hazard.
Asphyxiants (2)	There is a significant hazard associated with workers entering poorly ventilated areas (e.g. tanks) where oxygen may be deficient. An air supplied breathing apparatus may be required if adequate ventilation is not ensured.
Personal protective equipment guidelines	The recommendation for protective equipment contained within this SDS is provided as a guide only. Factors such as methods of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.
Health effects from exposure	It should be noted that the effects from exposure to this product will depend upon several factors including frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risk and apply control methods where appropriate.

16.2 Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS#	Chemical Abstract Service number – used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonised System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Dose, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
Mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	Related to hydrogen ion concentration using a scale of 0 (highly acidic) to 14 (highly alkaline)
ppm	Parts Per Million
STEL	Short Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

SDS Receipt Acknowledgement

I hereby acknowledge that I have been provided with a copy of the Origin Safety Data Sheet for Tempered LPG Issue 9, released 28 February 2019.

Name: _____

Title: _____

Company: _____

Customer Number: _____

Signed: _____

Dated: _____